Camion CTV OB 10

Specifications

GENERAL

Category :	XX Large
Maximum of Cameras :	28
Name of the Truck :	CTV OB 10 HD
Vehicle Type (Semi-trailer/ Coach) :	Expanding Trailer
Length with Tractor :	16,50 meter
Length without Tractor :	13,60 meter
Height :	4,00 meter
Width :	2,40 meter
Width when expanded :	6,00 meter
Weight :	45 tonnes
Voltage :	380/415 & 220/240 volt
Connector Type :	CEE 125 Amp 5 Pin or 3 x 125 Amp 3 pin

PRODUCTION

HD Vision Mixer :	Sony MVS8000 HD/SD 4M/E
HD Inputs (direct and 2nd Layer) :	80
Aux Buses HD :	48
DVE / Channels HD :	4 x DVE (Mixer Integrated)
Miscelaneous options :	EVS Shot Box / Abekas Clipstore with Lance Controller Sony MVS Satellite Mixer Panel
Monitors front :	8 x 42" NEC LCD with Evertz Multiviewers (total image 96)
Monitors rear :	5 x 17" Vutrix HD Plasma with Quad UMD (total image 20)

VISION

Synchronisers :	Axon 20/16 up/down converters
Monitors Vision :	7 x Sony BVM14HD Grade 1 + Vutrix Quadsplit Camera Preview
HD Cameras :	Sony HDC1500
HD Formats :	1080i 50 or 59.94 (60) Hz 1080P 23.97(24) or 25 or 29.97(30) Hz 720P 50 or 59.94(60) Hz
HD Highspeed Cameras :	Sony HDC3300 3 speed, Arri Hi-Motion, X-Mo on request
HD / SD Lenses :	Canon 11x, 14 x, 22x, 72x, 86x as required
Video Matrix HD :	Probel Cygnus HD 336 x 504 Multiformat

VTR

Monitors rear :	6 x 17" Vutrix HD LCD with Quad Split (total image 24)
Edit :	Full HD Linear Suite located in TSV Unit (upon request) Final Cut Pro on request Avid on request
Maximum Positions :	15
HD Type VTR / VDR :	Any HD / SD Format required
Monitors front :	24 x 17" Vutrix HD LCD with Quad UMD (total image 96)

Euro Media Group Tous droits réservés

SOUND

Audio Mixer Type :	Calrec Sigma OB Console
Inputs/Outputs :	56 in line faders with 320 DSP Channels 64 Analogue stereo Outputs
Surround Capabilities :	5.1 metering and surround monitor module RTW
Effects Type :	Neve, DBX
Speakers :	Genelec 1031 (5.1 Setup)
Monitors Audio :	13
Record/Replay :	CD Spot On Playback Hard Disc Shorcut (upon request)
Audio Matrix Type :	Probel 128 x128 AES with auto A>D and D>A
Type Multitrack Recording :	Upon Request
Communication Matrix :	Telex Adam 128x128
IFB System :	12 x RTS 2 ch. System
Beltpack :	20 x RTS 2 Channel
External Panels :	Minimum 2 x KP12, More upon request
ISDN Codec Interfaces :	Systembase upon request
Wireless :	3 x Duplex UHF basestations
Radio's TX/RX :	Minimum 12 x Motorola GP340 - More upon request